




RETROFIT TUBE

**T8 UNIVERSAL
4FT (48") CLEAR**



4' T8 CLEAR



SPECIFICATIONS

ELECTRICAL

MODEL	DESCRIPTION	POWER	POWER W/BALLAST	INPUT VOLTS	EFFICACY (LPW)	LIFETIME	POWER FACTOR
LR34195	LED13T8/30K/48/CL/UNV3	13	15.5	120-277 or Ballast	116	50,000	>0.9
LR34196	LED13T8/35K/48/CL/UNV3	13	15.5	120-277 or Ballast	116	50,000	>0.9
LR34197	LED13T8/40K/48/CL/UNV3	13	15.5	120-277 or Ballast	123	50,000	>0.9
LR34198	LED13T8/50K/48/CL/UNV3	13	15.5	120-277 or Ballast	123	50,000	>0.9
LR34199	LED13T8/65K/48/CL/UNV3	13	15.5	120-277 or Ballast	123	50,000	>0.9

PHOTOMETRIC


MODEL	COLOR (CCT)	TEMP	LUMEN	CRI
LR34195	3000K	SOFT WHITE	1900	83
LR34196	3500K	NATURAL	1900	83
LR34197	4000K	COOL WHITE	2000	83
LR34198	5000K	BRIGHT WHITE	2000	83
LR34199	6500K	DAYLIGHT	2000	83

GENERAL

FINISH	LENGTH	BASE	COST/YR	UL LISTED
CLEAR	4FT (48")	G13	\$ 1.57	YES
CLEAR	4FT (48")	G13	\$ 1.57	YES
CLEAR	4FT (48")	G13	\$ 1.57	YES
CLEAR	4FT (48")	G13	\$ 1.57	YES
CLEAR	4FT (48")	G13	\$ 1.57	YES

WIRING DIAGRAM

WITH BALLAST



DIRECT AC INPUT

A. SINGLE END INPUT



B. DOUBLE END INPUT

